

SA-6042UV

Customized Crystal Label Transfer Printer



UV Ink

C **M** **Y** **K** + **W** + Varnish

UV Direct
Print Effect

No Heating
Process Required

No Drying
Process Required

Good Adhesion
on Curved,
or Rugged Surface

Works well on various materials, such as plastic, glass, metal, ceramics, leather, wood, and other soft or hard materials.



720X900dpi A2 format size film can be printed in 5 minutes

The crystal label solution is a new technology of digital revolution. The advantage of this new technology is that it can be directly pasted and attached to the surface of the material to be transferred after printing, which is convenient and fast without other treatment.

• Technical Specifications

Model	SA-6042UV	
Printing Technology	Two I1600-U1 Print Heads	
Print Head	Piezoelectric Inkjet	
Acceptable Media	Size	600*420(mm)
	Width	≤600(mm)
Ink Curing Method	Thickness	≤1.5(mm)
	Type	Dual UV LED Lights
Ink Cartridges	Capacity	UV Ink
	Color	Siphon mode for color ink + regular stirring of white ink
Printing Resolution	Maximum 2400 dpi	
Power	3500W	
Interface	Ethernet Interface	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	69.76(W)x28.6(D)x55.9(H) in. (1772(W)x927(D)x1420(H) mm)	
Weight(with stand)	441 lb. (200 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridge, RIP software etc.	

