

SA-6090UVA


Multifunctional UV Flatbed Printer



Two I1600-U1/ I3200-U1 Heads

UV Ink

Ⓢ + ⓐ Ⓜ Ⓨ Ⓚ + Varnish



720X900dpi

Finish printing a 60cm*90cm sheet in 10 mins

Wide applications: suitable for surface decoration of various materials such as plastic, glass, wood, metal, leather, ceramics, etc



A printer designed for customization

The charming SA-6090UVA multi-functional flatbed printer can be used for not only sheet fed but also objects with non-flat surfaces, such as glass bottles, water cups, personalized mobile phone cases, gifts, promotional souvenirs, etc.

● Technical Specifications

Model	SA-6090UVA	
Printing Technology	Double I1600-U1/I3200-U1 Print Heads	
Print Head	Piezoelectric Inkjet	
Printing Width	600*900(mm)	
Acceptable Media	Width	≤600(mm)
	Thickness	≤180(mm)
Ink Cartridges	Capacity	Color Siphon + Regular Mixing of White Ink
	Color	W+CMYK+Varnish
Printing Resolution	Maximum 2400 dpi	
Speed	720x900dpi (Finish Printing a 600mm*900mm sheet in 10 mins)	
Ink Curing Method	Dual UV LED Lights	
Power	1300W	
Interface	Gigabit Ethernet	
Power Supply	AC 220V ± 5%, 16A 50HZ ±1	
Dimensions(with stand)	61.88(W)x57.48(D)x38.97(H) in.	
	(1572(W)x1460(D)x990(H) mm)	
Weight(with stand)	661 lb. (300 kg)	
Environment	Power on	Temperature: 59 F to 90 F [15 C to 32 C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 F to 104 F [5 C to 40 C] / Humidity: 20 to 80% (no condensation)


The electric cylinder fixture supports 360 ° rotation printing. With cylinder fixture installed on the flatbed, SA-6090UVA can print media up to 180mm height.




High quality output, simple and efficient operation
SA-6090UVA multifunctional flatbed contains many advanced functions to complete high-quality printing jobs with simple operations.



The overall printer cover can improve the operation safety, reduce the adhesion of dust in the printing process and ensure the printing quality.



High precision vacuum flatbed made of aluminum alloy with a turbofan installed below can fix the media firmly.



Up to 180mm media thickness. The beam can rise to 180mm to print customized products.